



AVVA PRO HDMI Extender / Splitter



R & B COMPUTER SYSTEMS LTD.

力衡電腦系統有限公司

2749 3325

www.rnb.com.hk
rnb@rnb.com.hk

Unit 1009, Global Gateway Tower, 63 Wing Hong Street, Cheung Sha Wan, Kln., HK
香港九龍長沙灣永康街 63 號 Global Gateway Tower 1009 室



EXTENDER	HDMI 50M Extender EX-50M-3D-IR2	HDMI 60M Extender EX-60M-3D-IR	HDMI 120M Extender EX-120M-TX / EX-120M-RX	HDMI HD BaseT Extender EX-100M-TX / EX-100M-RX	VGA Extender (100M) VGA-100E
Data transfer speed	6.75Gbps	6.75Gbps	4.95Gbps	10.0Gbps	350MHz@-3db
Transmission Distance	1080p up to 50m	1080p up to 60m	1080p up to 120m	1080p & 3D TV up to 100m, 4K to 60m	up to 100m
Resolution output	1080p, 1080i, 720p, 576p, 480p	1080p, 1080i, 720p, 576p, 480p, 3D Video Format	1080p, 1080i, 720p, 576p, 480p	1080p, 1080i, 720p, 576p, 480p, 3D Video Format, 4K x 2K	VGA, SVGA, XGA, SXGA, UXGA, LCD
Audio format support	DTS-HD Master Audio, Dolby True HD, Multi-Channel 5.1	DTS-HD Master Audio, Dolby True HD	DTS-HD Master Audio, Dolby True HD	DTS-HD Master Audio, Dolby True HD	3.5mm Stereo
Infra-RED	Bi-directional IR Transmission	One Way IR Transmission	One Way IR Transmission	One Way IR Transmission	N/A
Power supply	DC 5V	DC 5V	DC 5V	DC 5V	DC 9-12V
Power consumption (Max)	4W	3W	3W	5W	5W
Dimension (W x L x H)	85mm x 65mm x 25mm	85mm x 65mm x 25mm	95mm x 105mm x 25mm	72mm x 88mm x 25mm	105mm x 96mm x 28mm



SPLITTER	4 Ways HDMI Splitter Over Cat5e SP-14-Cat5e	HDMI Receiver RX-50	HDMI 2 Ways Splitter SP-12-4K	HDMI 4 Ways Splitter SP-14-4K	HDMI 8 Ways Splitter SP-18-4K
Data transfer speed	6.75Gbps	N/A	10.2Gbps	6.75Gbps	6.75Gbps
Transmission Distance	1080p up to 50m	1080p up to 50m	1080p up to 15m	1080p up to 15m	1080p up to 15m
Resolution output	1080p, 1080i, 720p, 576p, 480p	1080p, 1080i, 720p, 576p, 480p	Up to 4K x 2K (3840 x 2160), 3D TV Pass through	1080p, 1080i, 720p, 576p, 480p, 3D Video Format, 4K x 2K	DTS-HD TV 1080p, 1080i, 720p, 576p, 480p, Video Format, 4K x 2K
Audio format support	DTS-HD Master Audio, Dolby True HD, LPCM 7.1, AC3, DTSSD	DTS-HD Master Audio, Dolby True HD	DTS-HD Master Audio, Dolby True HD, LPCM 7.1	DTS-HD Master Audio, Dolby True HD, LPCM 7.1, AC3, DTSSD	DTS-HD Dolby True HD, LPCM 7.1, AC3, DSD
Infra-RED	N/A	N/A	N/A	N/A	N/A
Power supply	DC 5V	DC 5V	DC 5V	DC 5V	DC 5V
Power consumption (Max)	12W	5W	3W	10W	10W
Dimension (W x L x H)	185mm x 85mm x 40mm	83mm x 50mm x 25mm	75mm x 69mm x 25mm	115mm x 62mm x 25mm	270mm x 110mm x 35mm





AVVA PRO Matrix / Multi Viewer / Converter / Encoder / Selector / Repeater



MATRIX	HD Matrix 4 x 4 with RS232 & IR MX-404-RSIR-70	HDMI 70M Receiver with RS-232 RX-HD-70	HDMI Matrix 4 x 4 with EDID Selector MX-404-IR
Data transfer speed	6.75Gbps	6.75Gbps	2.25Gbps
Transmission Distance	1080p up to 70m	1080p up to 70m	1080p up to 15m
Resolution output	Up to 1080@60HZ@36.b/pixel, Support 3D	Up to 1080@60HZ@36.b/pixel, Support 3D RX232	1080p, 1080i, 720p, 576p, 480p, 576i, 480i, 3D Video
Audio format support	Support 7.1 Audio	Support 7.1 Audio	DTS-HD Master Audio, Dolby True HD
Infra-RED	Bi-directional IR Transmission	Bi-directional IR Transmission	IR Remote Control
Power supply	DC 12V	DC 12V	DC 5V
Power consumption (Max)	20W	20W	12W
Dimension (W x L x H)	445mm x 170mm x 45mm (1U Rack Size)	105mm x 100mm x 25mm	300mm x 100mm x 30mm

QUAD SCREEN MULTI-VIEWER



QSM-41HD	QSMM-41HD-USB
	
DC 12V	AC 100V to 240V
10W	25W
250mm x 118mm x 32mm	480mm x 100mm x 45mm (1U Rack Size)

Please feel free to Contact us for further details



OTHERS	Digital to Analog Audio Converter OPT-A2	HDMI to Audio Converter HDMI-HD-A2	H264 Encoder HD-VCB-1080	HDMI to AV Converter (RCA x 3) HDAV-3	Composit Video to HDMI Converter CTHD-1080	HD 4K 4 Ways Selector with IR SW-41-4K-IR	HDMI Repeater SX-50
Data transfer speed	N/A	6.75Gbps	2.25Gbps	N/A	N/A	10.2Gbps	1.65Gbps
Transmission Distance	N/A	1080p up to 15m	N/A	N/A	1080 up to 15m	1080p up to 15m	1080p up to 50m
Resolution output	N/A	1080p, 1080i, 720p, 576p, 480p	1080p, 1080i, 720p, 576p, 480p, 3D Video Format	1080p, 1080i, 720p, 576p, 480p, Video Format, CVBS, 480i, 576i	HDMI 720p or 1080p@50/60Hz	1080p, 1080i, 720p, 576p, 480p	N/A
Audio format support	RCA Stereo OUT	L/R + SPDIF 2 / 5.1 Channel	LPCM	RCA Stereo + Composit Video OUT		DTS-HD Master Audio, Doly True HD, LPCM 7.1	
Infra-RED						IR Remote Control	
Power supply	DC 5V	DC 5V	DC 5V	DC 5V	DC 5V	DC 5V	N/A
Power consumption (Max)	0.5W	3W	3W	1W	1W	3W	N/A
Dimension (W x L x H)	65mm x 41mm x 25mm	85mm x 66mm x 22mm	103mm x 70mm x 27mm	70mm x 65mm x 23mm	85mm x 90mm x 30mm	115mm x 62mm x 25mm	50mm x 26mm x 13mm